

## KA7230S

PS/2-USB Console Module



The KA7230S Console Module offers secure access to the servers in a Matrix KVM Switch ( [KM0932/KM0532](#)) from a PS/2 or USB console (monitor, keyboard, and mouse) up to 200 meters away. It provides an extra computer port for integration with a computer workstation, enabling users to seamlessly switch between the local computer and the servers in the Matrix KVM Switch. The KA7230S also features an intuitive graphical user interface, the Graphical OSD, with easy-to-use menus and icons that enable easy access and efficient management.

KA7230S has a built-in RS-232 port. Administrators can establish a serial terminal login to the Console Module in order to control the KVM port access for all consoles connected to switch – any console can be assigned to access any KVM port from a single interface point. This function is extremely useful in large data centers where the display of all the consoles can be projected onto a wall for easy viewing of all operations, and the entire installation can be monitored on a port-by-port basis

### Features

- One Combo Graphic Console Module can control a local computer and a matrix KVM switch ( [KM0932/KM0532](#))
- Supports PS/2 and USB keyboards and mice (Console)
- Switch between your workstation computer and the matrix KVM switch
- Graphical OSD-intuitive, easy-to-use graphical On Screen Display to manage servers
- RS-232 port login support permits an administrator to control the KVM port access for all consoles connected to switch – any console can be assigned to access any KVM port from a single interface point
- Connects to matrix KVM switch via Cat 5e/6 cable
- Superior Video Quality – 1920 x 1200 @ 60 Hz up to 150 meters; 1280 x 1024 @ 60 Hz up to 200 meters
- Manual video gain control for fine tuning
- Convenient computer selection via intuitive hotkey combinations or graphical OSD menus
- Firmware upgradeable

### Specifications

|                      |  |
|----------------------|--|
| Computer Connections | 1  |
| Console Connections  | 1  |
| Port Selection       | GUI, Hotkey  |
| Connectors           |  |
| Console Ports        | 2 x USB Type A Female (White)<br>1 x 6-pin Mini-DIN Female (Purple)<br>1 x 6-pin Mini-DIN Female (Green)<br>1 x HDB-15 Female (Blue) |

|                         |  |
|-------------------------|--|
| Local Computer KVM Port | 1 x SPHD-17 Female (Yellow)  |
| KVM Switch Ports        | 2 x RJ-45 Female   |
| RS-232                  | 1 x DB-9 Male (Black)  |
| Power                   | 1 x DC Jack  |
| Switches                |  |
| Firmware Upgrade        | 1 x Slide  |
| Video Gain Adjustment   | 2 x Pushbutton   |
| Selection               | 1 x Pushbutton (Local/Remote)  |
| LEDs                    |  |
| Power                   | 1 (Blue)   |
| Online                  | 1 (Green)  |
| Local                   | 1 (Orange)   |
| Remote                  | 1 (Orange)   |
| Emulation               |  |
| Keyboard / Mouse        | PS/2; USB (PC, Sun, Mac)   |
| Video                   | 1920x1200@60Hz (150 m); 1280x1024@60Hz (200 m)   |
| Scan Interval           | 1-240 Seconds  |
| Power Consumption       | DC5.3V:6.12W:37BTU/h<br><br>Note:<br><ul style="list-style-type: none"> <li>● The measurement in Watts indicates the typical power consumption of the device with no external loading.</li> <li>● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.</li> </ul> |
| Environmental           |  |
| Operating Temperature   | 0 - 50°C   |
| Storage Temperature     | -20 - 60°C   |
| Humidity                | 0-80% RH, Non-condensing   |
| Physical Properties     |  |
| Housing                 | Metal  |
| Weight                  | 1.22 kg ( 2.69 lb )  |
| Dimensions (L x W x H)  | 22.71 x 17.15 x 5.48 cm<br>(8.94 x 6.75 x 2.16 in.)  |
| Note                    | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.  |

Diagram



**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their respective owners.