

## CS62T

2-Port USB VGA KVM Switch with File Transfer and Audio



The CS62T improves on prior models in the Cable KVM series, by combining a 2-port KVM switch enabling it to provide USB peripheral sharing and USB file sharing between the connected computers – ideal for syncing files, folders between portable and desktop computers. Featuring an unbeatable combination of USB peripheral sharing, USB file management, audio support for multimedia and user-friendly operation, the CS62T offers the utmost in desktop KVM switching functionality.

[Bookmark and Share](#)

### Features

- One USB console controls two USB interface computers
- [USB File Management](#) -transfer files between connected Windows based computers - sync files, folders
- USB mouse port can be used for USB hub and USB peripheral sharing
- Computer selection via hotkeys and mouse\*
- Hotkey selection for OS and keyboard language
- Audio-enabled - full bass response for 2.1 surround sound
- Multiplatform support - Windows, Linux, Mac, and Sun
- Compact design, built-in all-in-one cables (2 x 0.9 m)
- [Video DynaSync™](#) - exclusive ATEN technology which eliminates boot-up display problems and optimizes resolution when switching between ports
- Power on detection - automatically switches to the first powered on computer
- Superior video quality - up to 2048 x 1536; DDC2B
- [Supports gaming and multimedia keyboards](#)
- Supports multifunction and wireless keyboards and mice
- Mac/Sun keyboard support and emulation\*\*
- Auto Scan function to monitor computer operation
- Non-powered

\* Mouse port switching is only supported when using a USB 3-key wheel mouse

\*\* 1. PC keyboard combinations emulate Sun/Mac keyboards

2. Sun/Mac keyboards only work with their own computers

## Specification

|                        |                                                                                                                                        |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Computer Connections   | 2                                                                                                                                      |
| Port Selection         | Hotkey, Mouse                                                                                                                          |
| Connectors             |                                                                                                                                        |
| Console Ports          | 2 x USB Type A Female (White)<br>1 x HDB-15 Female (Blue)<br>1 x Mini Stereo Jack Female (Green)<br>1 x Mini Stereo Jack Female (Pink) |
| KVM Ports              | 2 x USB Type A Male (Purple)<br>2 x HDB-15 Male (Blue)<br>2 x Mini Stereo Jack Female (Green)<br>2 x Mini Stereo Jack Female (Pink)    |
| File Transfer          | 2 x USB Type A Male (Black)                                                                                                            |
| Cable Length           |                                                                                                                                        |
| Computer               | 2 x 0.9 m                                                                                                                              |
| Emulation              |                                                                                                                                        |
| Keyboard / Mouse       | USB                                                                                                                                    |
| Video                  | 2048 x 1536; DDC2B                                                                                                                     |
| Scan Interval          | 3, 5, 10, 20 secs. (default 5 secs.)                                                                                                   |
| Environmental          |                                                                                                                                        |
| Operating Temperature  | 0 - 50°C                                                                                                                               |
| Storage Temperature    | -20 - 60°C                                                                                                                             |
| Humidity               | 0-80% RH Non-condensing                                                                                                                |
| Physical Properties    |                                                                                                                                        |
| Housing                | Plastic                                                                                                                                |
| Weight                 | 0.42 kg                                                                                                                                |
| Dimensions (L x W x H) | 8.24x6.99x2.52cm                                                                                                                       |
| Note                   | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.        |

## Diagram



### **ATEN International Co., Ltd.**

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their  
 respective owners.