

## CS1208DL / 1216DL

8/16-Port Slideaway LCD KVM Switch



The power supply of CS1208DL/CS1216DL supports DC-36V-72V. To industries using specific racks, such as the data communication industry, this function fulfills the power supply needs of the rack from KVM Switches.

20050912132331001.jpg

### Features

- Daisy chain up to 31 additional CS-1216A series unit - control up to 512 computers from the unit's Slideaway console.
- Neat high-quality cable for the high-density server rack.
- No software required - convenient computer selection via intuitive hotkey combination or On Screen Display (OSD) menu- OSD port list automatically expands when stations are added.
- Security - administrator / user password authorization for enhanced security protection (PSP), administrator synchronized confirmation between first and chained stations.
- Two types of logout :manual and timed.
- Detachable modular KVM switch for easy maintenance.
- DDC emulation VGA setting of every connected computer are automatically adjusted for optimal output to the LCD monitor.
- Supports special DC -36V to -72V power supply.
- Drawer access lock - an easy to use feature that enables the Slideaway's console drawer to remain securely locked away in position when not in use.
- Rack mountable in a 19" (1U) system rack with a depth of up to 36 inches.
- Buzzer ON/OFF via hotkey and OSD.
- Broadcast Mode: Operations simultaneously performed on all selected computers, software installation and upgrading, system wide shutdown...etc.
- A-Grade TFT LCD Panel.
- Multiplatform support:DOS, Windows 2003/ 2000/XP/98/ME/NT and Linux.

### **ATEN International Co., Ltd.**

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan

Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their respective owners.