

## PE0112

Basic PDU Series

PE0112A



The PE0112 series Basic PDU contains 12 AC outlets and is available in IEC or NEMA socket configurations. The PE0112 series Basic PDU features a space-saving 1U design that allows it to be mounted vertically on the outside of a rack, resulting in a more efficient use of space in the server room, while providing 12 AC outlets.

### Features

- **Basic PDU**
  - Space saving -1U rack mount design
  - IEC or NEMA outlet models
  - Aluminum material
- **Typical Applications**
  - Servers
  - Network Devices
  - Telecom Equipment

### Specification

| Function              | PE0112A                                        | PE0112G     |
|-----------------------|------------------------------------------------|-------------|
| Electrical            |                                                |             |
| Nominal Input Voltage | 100-120 VAC                                    | 100-240 VAC |
| Maximum Input Current | 15A(Max)<br>(UL de-rated 12A Max)<br>(PSE 10A) | 10A(Max)    |
| Input Frequency       | 50-60 Hz                                       | 50-60 Hz    |
| Input Connection      | NEMA 5-15P                                     | IEC-320 C14 |

|                                    |                                                                                                                                                                      |                                                                                                                                                                      |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Input Power                        | 1800VA(MAX) ;<br>1440VA(UL de-rated)                                                                                                                                 | 2400 VA(Max)                                                                                                                                                         |
| Outlet Type                        | (12) NEMA 5-15R                                                                                                                                                      | (12) IEC 320 C13                                                                                                                                                     |
| Nominal Output Voltage             | 120 VAC                                                                                                                                                              | 240V                                                                                                                                                                 |
| Maximum Output Current (Outlet)    | 15A(Max)<br>(UL de-rated 12A Max)<br>(PSE 10A)                                                                                                                       | 10A(Max)                                                                                                                                                             |
| Maximum Output Current (Bank)      | 15A(Max)<br>(UL de-rated 12A Max)<br>(PSE 10A)                                                                                                                       | 10A(Max)                                                                                                                                                             |
| Maximum Output Current (Total)     | 15A(Max)<br>(UL de-rated 12A Max)<br>(PSE 10A)                                                                                                                       | 10A(Max)                                                                                                                                                             |
| OPD(Overcurrent Protection Device) | Yes                                                                                                                                                                  | Yes                                                                                                                                                                  |
| Physical Properties                |                                                                                                                                                                      |                                                                                                                                                                      |
| Dimensions (L x W x H)             | 48.20 x 4.44 x 4.50 cm<br>(18.98 x 1.75 x 1.77 in.)                                                                                                                  | 48.20 x 4.44 x 4.50 cm<br>(18.98 x 1.75 x 1.77 in.)                                                                                                                  |
| Weight                             | 0.65 kg ( 1.43 lb )                                                                                                                                                  | 0.65 kg ( 1.43 lb )                                                                                                                                                  |
| Power Cord Length                  | 10ft(14#)                                                                                                                                                            | 10ft(3×1.0mm2)                                                                                                                                                       |
| Environmental                      |                                                                                                                                                                      |                                                                                                                                                                      |
| Temperature (Operating / Storage)  | 0 – 40°C / -20 – 60°C<br>*When the environmental temperature comes close 40 degrees, it is recommended to lower the load to 60% to comply to the safety regulations. | 0 – 40°C / -20 – 60°C<br>*When the environmental temperature comes close 40 degrees, it is recommended to lower the load to 60% to comply to the safety regulations. |
| Elevation (Operating / Storage)    | 3000m                                                                                                                                                                | 3000m                                                                                                                                                                |
| Compliance                         |                                                                                                                                                                      |                                                                                                                                                                      |
| EMC Verification                   | FCC Class A                                                                                                                                                          | CE Class A                                                                                                                                                           |
| Safety Verification                | UL                                                                                                                                                                   | CE,LVD, UL                                                                                                                                                           |
| Note                               | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.                                      |                                                                                                                                                                      |

**Diagram****ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan

Phone: 886-2-8692-6789 Fax: 886-2-8692-6767

www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their  
respective owners.