

VE781010

10 m True 4K HDMI Active Optical Cable (True 4K@10 m)



ATEN VE781010 True 4K HDMI Active Optical Cable utilizes AOC technology that enables conversion between input signals and optical signals for optimum high bandwidth data transmissions. The EMI-resistant optical cables come in 10 m with full support of True 4K resolutions. It is fully compliant with HDCP 2.2 standards and meets HDMI specifications including 3D, deep color, and data rates up to 18 Gbps. Supported Dolby True HD and DTS-HD Master Audio, the optical cables guarantee lossless audio signal transmissions. The VE781010 optical cable is an ideal solution for extending the reach of your digital signage in a wide range of settings, such as traffic stations, shopping centers, and hospital facilities.



Features


- Supports resolution up to True 4K (4096 x 2160 @ 60Hz 4:4:4)
- HDMI (3D, Deep Color, True 4K, HDR, ARC); HDCP 2.2 compliant
- Extends True 4K signals up to 10 m
- Reduced EMI and RFI for lower noise interference
- High data transfer rate of 18 Gbps
- Supports multi audio channel – Dolby TrueHD and DTS-HD Master Audio
- Robust cable pulling strength (Max.10 kg) and compression load resistance (Max.50 kg)
- Plug-and-play

Specification

Cable Length	10M / 32.8ft
Cable Type	Hybrid type with optical fiber (OM3) and copper wire
Video Input	
Interfaces	1 x HDMI 19-pin Type-A Male
Video Output	
Interfaces	1 x HDMI 19-pin Type-A Male
Video	
Max. Data Rate	18 Gbps (6 Gbps per Channel)

Max. Pixel Clock	600 MHz (Max.)
Max. Resolutions / Distance	Up to 4096 x 2160 / 3840 x 2160 @60Hz (4:4:4) / 10M *Color sub-sampling: 4:4:4 / 4:2:2 / 4:2:0 *Color Depth: 30 / 36 / 48 bit
Compliance	HDMI (3D, Deep Color, 4K, HDR, ARC) HDCP 2.2
Communication	
Signals	TMDS / HDCP 2.2 / EDID / CEC
Audio	
Input	PCM 8-channel, Dolby Digital True HD, DTS-HD Master Audio
Output	PCM 8-channel, Dolby Digital True HD, DTS-HD Master Audio
Conductor	
Construction	7 x Tinned Copper wire strand 4 x OM3 Optical Fiber (50/125um)
Notification	Bend Radius: 20mm (Min.) Compression Load Resistance: Max. 50kg (500N) Cable Filler: Kevlar Cable Marking: ATEN INTERNATIONAL --- HIGH SPEED HDMI HYBRID ACTIVE OPTICAL CABLE 4K@60Hz 18Gbps -- PVC CE EU RoHS EC ZONE/DEVICE * NO external power required
Certifications	
Certifications	Safety and Emission: CE / FCC / RoHS / REACH / UL VW-1 EMC Class-A / Class-B
Power Consumption	DC5.0V:0.25W:0.05ABTU/h Note: ● The measurement in Watts indicates the typical power consumption of the device with no external loading. ● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.
Jacketed	
Material	PVC (85P) Color: Black
Environmental	
Operating Temperature	0°C to 50°C (32°F to 122°F)
Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Humidity	0 - 85% RH, Non-Condensing
Physical Properties	
Housing	Connector Case: Zinc Alloy
Weight	0.35 kg (0.77 lb)
Cable Outer Dimension	4.5mm (± 0.2mm)
Carton Lot	5 pcs

Diagram



HDMI™
HIGH-DEFINITION MULTIMEDIA INTERFACE

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.