

## 2L-2503

3M VGA Cable



The VGA Cable is designed to provide a high quality VGA connection, ideally suited for high resolution applications up to 1920 x 1200. This durably constructed VGA video cable eliminates the picture ghosting and fuzzy images, guaranteeing users the ultimate A/V experiences.

### Features

- Optimized for analog signal transmission
  - VGA cable with 15-pin male input and output
  - Bend Radius: 60°\*
  - Outer shielded material: Al Mylar tape
  - Compatible with ATEN VGA products
- Note:\* Swings 3000 times between angles of +/- 60 degrees, at a frequency of 40 times per minute

### Specification

|                    |                                    |
|--------------------|------------------------------------|
| Conductor          |                                    |
| Material           | Tinned Copper                      |
| Conductor Diameter | 30 AWG                             |
| Jacketed           |                                    |
| Material           | Jacket: PVC<br>Shielding: AL-Mylar |
| Connectors         |                                    |
| Video              | HDB-15 Male<br>HDB-15 Male         |
| Cable Length       | 3 m                                |



Simply Better Connections

***ATEN International Co., Ltd.***

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
All rights reserved. All other trademarks are the property of their  
respective owners.