

## KA7174

KVM Adapter Module with USB, PS/2, and RS-232 Local Console



KA7174 KVM Adapter Module is designed to provide a convenient local console connection in a KVM over IP switch or matrix KVM installation. KA7174 allows a PS/2, USB, or RS-232 server to be connected to an ATEN KVM over IP switch via Cat 5e / 6 cable while providing an extra local console connection supporting USB or PS/2 keyboard and mouse, monitor, and / or RS-232 touch panel for convenient local operation. In addition, the KA7174 also features Privileged Console Control function with OSD tag notifications indicating denial of access to the local or remote users when configured as such.

By installing the [2XRT-0015G](#) KVM over IP Access Control Box to the KA7174, users can easily enable or disable remote over IP control privilege from the KVM over IP switch simply by pressing the control button on the [2XRT-0015G](#) – making operation only permitted to the user at the local console.

### Features

- Compatible with ATEN [2XRT-0015G](#) KVM over IP Access Control Box to initiate local-only access and control to the servers
- Cat 5e / 6 cable connects the device and KVM switch
- Supports computers with PS/2 and USB keyboards and mice, controlling the system from these extended devices and monitor via local console
- Supports custom RS-232 touch panel from both local and remote sites
- Pushbutton operating mode selection for privileged console control with OSD tag notifications indicating denial of access to the local or remote users when configured as such
- Built-in ASIC for greater stability and compatibility
- USB over-current detection and prevention
- Built-in ESD protection and surge protection
- Superior video quality – supports resolution up to 1920 x 1200 (reduced blanking)\*
- Supports VGA , SVGA , SXGA , UXGA , WUXGA , and multisync monitors; local monitor supports DDC, DDC2, and DDC2B
- Easy to install – no software required – simply connect cables to the devices

\* This maximum resolution may vary depending on the transmission distance. For more details, please refer to the product pages of the connected KVM switches.

**Specifications**

|                          |  |
|--------------------------|--|
| Connectors               |  |
| Console Ports            | 1 x SPHD Male (Yellow)   |
| KVM Ports                | 1 x SPHD Female (Yellow)   |
| Power                    | 1 x DC Jack (Black)  |
| Control                  | 1 x 6-pin Mini-DIN Female (Purple)<br>1 x RJ-11 Female + 1 x USB Type A Female (Black)   |
| RS-232                   | 1 x DB-9 Male (Black)<br>1 x DB-9 Female (Black)   |
| Link                     | 1 x RJ-45 Female (Black)   |
| Pushbuttons              |  |
| Operating Mode Selection | 1 x Pushbutton   |
| LEDs                     |  |
| Local                    | 1 (Green)  |
| Remote                   | 1 (Green)  |
| Emulation                |  |
| Keyboard / Mouse         | PS/2, USB  |
| Video                    | Up to 1920 x 1200 @ 60Hz   |
| Power Consumption        | DC5V:1.57W:30BTU/h<br><br>Note:<br>● The measurement in Watts indicates the typical power consumption of the device with no external loading.<br>● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded. |
| Environmental            |  |
| Operating Temperature    | 0 - 50°C   |
| Storage Temperature      | -20 - 60°C   |
| Humidity                 | 0–95% RH, Non-condensing   |
| Physical Properties      |  |
| Housing                  | Metal  |
| Weight                   | 0.49 kg ( 1.08 lb )  |
| Dimensions (L x W x H)   | 20.30 x 8.64 x 2.50 cm<br>(7.99 x 3.4 x 0.98 in.)  |
| Note                     | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.  |

Diagram

