

OL1000LV

Professional Online UPS 100V / 110V / 120V / 127V 1000VA



The ATEN Professional [Online UPS](#) is an exceptional and innovative electrical apparatus that provides emergency power to a load when the input power source, or the main one, fails. The basic technology of an [online UPS](#) is the same as in a standby or line-interactive UPS, however, the ATEN Professional [Online UPS](#) provides a much greater current of AC-to-DC battery-charger / rectifier where the rectifier and inverter are designed to run continuously with improved cooling systems.

In all our years of working with computers, we've found the vast majority of hardware failures can be directly attributed to the stress hardware components experience during the shut-down and startup process, especially if power surges or blackouts are involved. With severe weather, the aging electrical grid, and hazards lurk inside users' own walls, their equipment is under constant attack from power problems. Even a brief loss of power, sags, or a momentary surge can ruin users' equipment and destroy irreplaceable data. Desktop computers don't have batteries built-in like laptops do. If users are working on a desktop during a power outage, the system would come to an immediate halt. Not only would users lose their work, but the process imposes unnecessary stress on their machine.

If a UPS is present and a power loss occurs, the batteries in the UPS would keep the power steady and unchanged. The ATEN Professional [Online UPS](#) adjusts incoming AC power, provides [battery backup](#) to pass through most outages, and saves open files automatically. When power is restored, the UPS begins recharging its batteries.

The [Online UPS](#) unit continuously filters wall power through the battery system. Since the attached electronics run completely off the battery (that are always topped off by the external power supply), there is never a single millisecond of power interruption when there is power loss or voltage regulation issues. The [Online UPS](#) unit thus acts as an electronic firewall between users' devices and the outside world by stabilizing all the electricity to which users' devices are exposed.

The UPS has one USB port and one serial port that allow connection and communication between the UPS and the connected computer. Power management software installed on the connected computer(s) gives IT professionals the tools they need to easily monitor and manage their backup power. This advanced software allows users to access vital UPS battery conditions, load levels, and runtime information as well as provide unattended shut down of network computers and virtual machines connected to a [battery backup](#) during a power event.

The ATEN Professional [Online UPS](#) offers a different way to access detailed UPS settings and information with an LCD screen. The illuminated LCD screen displays input voltage, battery capacity, and more, and includes a three-button configuration interface and audible alarms for different modes of operation.

Note: When any battery pack, provided or purchased separately, is not in use, please recharge it for 4 ~ 6 hours every 3 ~ 6 months.

Features

- True double-conversion – output power factor is 1 (maximum), which means all of the power supplied is being used for productive work and makes work the most efficient.
- Output voltage regulation < 1% – provides higher performance and efficiency for critical applications.
- Programmable power management outlets – users can easily and independently control load segments. During power failure, this feature enables users to extend battery time to mission-critical devices by shutting down noncritical devices
- Emergency Power Off function (EPO) – EPO connector at rear panel allows emergency UPS Power Off from a remote location
- SNMP + USB + RS-232 multiple communications – allows either USB or RS-232 communication ports to work with SNMP interface simultaneously
- Hot swappable battery design – all potential UPS maintenance, including complete power module exchange, can be performed without powering down connected equipment. As long as utility power is on, users can leave the UPS and connected equipment on while replacing the battery
- ECO mode for energy saving – offers up to 97% efficiency to cut energy usage and cost. UPS power application via static bypass timely returns to online [double conversion](#) when the need arises
- Provides over-voltage cut-off protection and surge immunity by MOV for full-time equipment protection
- High power factor charger up to 1000W capacity with very low ripple current when charging battery
- Multi-functional LCD interface – displays immediate, detailed information on input voltage, battery capacity, power status, battery status, operating status, and assessed backup runtime, etc
- Smart battery charger design to optimize battery performance – adjusts charging voltage according to outside temperatures and extends the useful service life of batteries

Specifications

| | |
|-------------------------------|--|
| General | |
| UPS Topology | Double-Conversion |
| Energy Saving(max) | >96%(ECO) >89%(AC) >88%(Batt) |
| HID Compliant USB Port | Yes |
| Serial Port | Yes |
| SNMP / HTTP Remote Monitoring | Yes - Optional SNMP CARD |
| Input | |
| Voltage | 100/110/115/120/125/127V (127 V AC not applicable for U.S. region) |
| Input Voltage Range | 80-150 V AC \pm 5% @ 100% load 55-150 V AC \pm 5% @ 50% load Derate capacity to 80% when the output voltage is adjusted to 100 VAC |
| Input Frequency Range | 40 Hz ~ 70 Hz |
| Rated Input current | 9.3A |
| Input Power Factor | \geq 0.99 @ nominal voltage (100% load) |
| Cold Start | Yes |
| Plug Type | NEMA 5-15P |
| Power cord | 6 ft |
| Output | |
| VA | 1000 |
| Watts | 1000 |

| | |
|-------------------------------------|---|
| On Battery Waveform | Sine Wave |
| On Battery Frequency | 50/60Hz +/- 0.1 Hz |
| Outlets - Total | 8 |
| Outlet Type | (8) NEMA 5-15R |
| Outlets - Battery & Surge Protected | 8 |
| Rated Power Factor | 1 |
| Crest Factor | 03:01 |
| Harmonic Distortion | $\leq 2\%$ THDv(Linear Load) $\leq 4\%$ THDv (Non-linear Load) |
| Voltage Regulation | $\pm 1\%$ (Batt) |
| Transfer Time(AC to Batt.) | 0ms |
| Transfer Time(Inverter to Bypass) | 4ms(ECO) |
| Battery | |
| Runtime at Half Load (min) | 9.44 (TUV) 10.1 (UL) |
| Runtime at Full Load (min) | 3.1 (TUV) 2.95 (UL) |
| Battery Type | Sealed Lead-Acid |
| Battery Pack Voltage | 24V |
| Battery Size | 12V/9AH |
| Battery Quantity | 2 |
| Hot-Swappable | Yes |
| Typical Recharge Time | 3 hours recover to 95% capacity @2A charging current. Max charger current 8A |
| Extended Battery Module | BP24V18AH |
| Replacement Battery Pack | BC24V9AH |
| Replacement Battery Pack Quantity | 1 |
| Physical Properties | |
| Rack Unit | 2U |
| Type | Rack/Tower |
| Dimensions (L x W x H) | 8.80 x 43.80 x 41.00 cm (3.46 x 17.24 x 16.14 in.) |
| Weight | 12.90 kg (28.41 lb) |

| | |
|--|--|
| Environmental | |
| Temperature (Operating / Storage) | 0–40°C (non-condensing) / -20 – 50°C |
| Humidity (Operating & Storage) | 20–90 % RH / 10% – 95%(No condensing) |
| Audible noise at 1M from surface of unit | Less than 50dB |
| Certifications | |
| Certifications | cTUVus (TUV) UL (UL) |
| Approvals | VCCI, BSMI, FCC Class A, RoHS |
| Package Contents | 1×Online UPS 1×Rack Mounting Kit Set 1×Rail Slide Kit Set 1×RS-232 Cable 1×USB Type A to B Cable 1×User Manual 4×Tower Stand |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.