

FH600

6-포트 FireWire 허브



The FH600 IEEE 1394 Hubs provide six 1394a compliant ports that support data transfer rates of 100, 200, and 400 Mbps. Each port automatically switches to the highest speed that the peripheral supports. Each IEEE 1394 peripheral connects externally; simply plug in the cables. Configuration is automatic; there is no need to specify memory addresses, IRQ assignments, device IDs, or even plug in terminators. The advantages of hot pluggable connectivity and non interrupting daisy chaining has distinguished FireWire as a household standard.



특장점

- 6 IEEE 1394 ports for more convenient adding and removing of devices.
- IEEE 1394, IEEE 1394a Compliant.
- 100, 200, 400 Mbps data transfer rate; automatically uses the highest speed the peripheral supports.
- Supports hot plugging.
- 6 pin IEEE 1394 I/O connectors.
- DC input terminal for optional external power supply.
- OS Support: Windows 2000, Windows XP, [Windows Vista](#), Mac and FreeBSD

사양

포트	6
커넥터	
USB 포트	6 x 6 pin IEEE 1394 Std. (Black)
전원	1 x DC Jack (Black)
LED	1 (Orange)
Data Rate	100 / 200 /400 Mbps (Asynchronous, Isochronous)
일반 지원	IEEE 1394a
소비 전력	DC 9V, 0.15W 노트: ● 와트 단위의 측정은 외부 부하가 없는 장치의 일반적인 전력 소비를 나타냅니다. ● BTU/h 단위의 측정값은 장치가 완전히 로드되었을 때 장치의 전력 소비를 나타냅니다.
사용 환경	
사용 온도	5°-40°C
보관 온도	-20°-60°C
습도	0 ~80% RH, Non-condensing
제품 외관	
재질	Plastic
무게	0.11 kg (0.24 lb)
크기 (L X W X H)	10.09 x 9.14 x 3.33 cm (3.97 x 3.6 x 1.31 in.)
노트	일부 랙 마운트 제품은,WxDxH의 표준 물리적 치수를 LxWxH 형식으로 사용하고 있습니다.

다이어그램



에이텐 코리아 ATEN KOREA

서울시 금천구 디지털로9길 32(가산동) 갑을그레이트밸리 B동 303호
Tel: 02-467-6789 Fax: 02-467-9876
www.aten.com/kr/ko E-mail: marketing@aten.co.kr



© Copyright 2025 ATEN® International Co., Ltd.
ATEN and the ATEN logo are registered trademarks of ATEN International Co., Ltd.
All rights reserved. All other trademarks are the property of their respective owners.