

## VK236

6-Port IR/Serial Expansion Box



The VK236 provides Ethernet-to-IR/serial connectivity with 6 IR / serial ports. It allows users to remotely access IR / serial devices from a PC or any system located anywhere. The complete Telnet CLI commands are fully integrated into users' commercial and industrial applications.

What's more, the VK236 serves as a flexible expansion box of the ATEN Control System, enabling users to control additional IR / serial devices through an ATEN controller in any environments where more devices are required. With the advantage of Ethernet-based connection, the expansion box can be easily connected to controllers via LAN connection from a variety of locations across a network.

### Accessories:

\*The power adapter for this product is sold separately. For more information about this accessory, see [Accessories](#).


### Features

- An Ethernet-to-IR / serial box ships with 6 IR / serial ports
- Supports Power over Ethernet (PoE) or DC power supply
- Supports IEEE 802.1x authentication protocol for enhanced network security
- Supports Telnet CLI (command-line interface) mode for third-party system integration
- Supports Pronto formatted IR codes- IR command codes can be entered in Hex format
- WebUI provides VK236 system information, including firmware upgrade
- An expansion solution for connecting more IR / serial devices to ATEN Control System
- Flexible deployment via Ethernet connection
- Works with a connected ATEN controller with ID Switch through instant configuration

Specifications

Interfaces	
IR/Serial	<p>6 x Programmable IR / Uni-directional RS-232 Port          6 x 2-Pole Terminal Block Connector          IR: TTL level (0 to 5 V)          – Carrier Frequency: 10KHz~455KHz;          Serial: Uni-directional RS-232 ( + - 5 V)          – Baud Rate: 300 to 115200 (default: 9600);          – Data Bit: 8 (default) or 7;          – Stop Bit: 1 (default) or 2;          – Parity: None (default), Even or Odd</p>
Ethernet	<ul style="list-style-type: none"> <li>• 1 x RJ-45 Female, 10/100Base-T</li> <li>• Supported Protocol: ARP, ICMP, TCP/IP, DHCP, HTTPS, SSH</li> <li>• DHCP-enabled. The following default IP settings will be used if no IP is assigned within 30 seconds:              IP: 192.168.0.60              Subnet Mask: 255.255.255.0</li> </ul>
Switches	
Controller ID	1 x 16-segment Switch
Expander ID	1 x 8-segment Switch
Reset Button	1 x Semi-recessed Pushbutton
USB	1 x USB Type A (Firmware upgrade only)
Power Consumption	<p>DC5V:1.31W:17BTU/h          DC48V:1.64W:18BTU/h</p> <p>Note:          ● The measurement in Watts indicates the typical power consumption of the device with no external loading.          ● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded.</p>
Environmental	
Operating Temperature	0 – 50°C
Storage Temperature	-20 – 60°C
Humidity	0 - 80% RH, Non-Condensing
Physical Properties	
Housing	Metal
Weight	0.45 kg ( 0.99 lb )
Dimensions (L x W x H)	13.00 x 7.58 x 4.20 cm (5.12 x 2.98 x 1.65 in.)
Note	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.

Diagram



**ATEN International Co., Ltd.**

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their respective owners.