

VM5808D

8 x 8 DVI Matrix Switch with Scaler



reddot award 2015
winner interface design



While HDMI-compliant devices are becoming more popular, the majority of traffic control centers and other large-scale, centralized control rooms still rely on DVI display devices.

In order to avoid signal instability, quality deterioration and other factors associated with interface converters, ATEN created the VM5808D: A seamless matrix switch for DVI signals that offers an easy and affordable way to route any of 8 DVI video sources to any of 8 DVI displays.

The VM5808D includes seamless switching that employs an FPGA matrix architecture to ensure continuous video streaming, real-time control and stable signal transmission. With a built-in high-performance scaler, the VM5808D easily converts various input resolutions into a array of output resolutions, giving viewers the best image quality across all displays. The switch also integrates video wall functionality with an easy-to-use web GUI that lets you create 16 connection profiles for convenient layout customization.

The VM5808D is the ideal solution for any control center streaming multiple sources to multiple displays.



Features

- 8 x 8 DVI I/O connections
- Configuration and Control via pushbuttons / IR Remote Control
- View and control via [ATEN Video Matrix Control App](#) in a swift and agile way
- System Operation via bi-directional RS-232 serial controller / Browser Graphical User Interface (GUI) / Telnet
- Extends IR transmission via IR extension cable
- Built-in Scaler on each output port converts input resolutions into the display's native resolution, supports scaling 1920 x 1200 resolutions up or down
- Seamless Switch™ – ATEN FPGA design unifies video formats to provide continuous video streams, real-time switching and stable signal transmissions *
- Video Wall – features up to 16 video wall profiles for custom screen layouts via point-n-click web GUI *
- EDID Expert – configures optimum EDID settings for smooth power-up, high-quality display and use of the best resolution across different screen
- Firmware Upgradeable
- Rack Mountable (1U Design)

Note:

1. If Seamless Switch is enabled, the video output will not display 3D, Deep Color, or interlace (i.e., 1080i) resolution features. To use these features, you must disable Seamless Switch.
2. Videos may not display within range when Seamless Switch™ or Video Wall is enabled, in which case please adjust the display settings on your device.

Specifications

| | |
|----------------------------|--|
| Video Input | |
| Interfaces | 8 x DVI-D Female (White) |
| Impedance | 100 Ω |
| Max. Distance | 1.8 m |
| Video Output | |
| Interfaces | 8 x DVI-D Female (White) |
| Impedance | 100 Ω |
| Video | |
| Max. Data Rate | 6.75 Gbps (2.25 Gbps Per Lane) |
| Max. Pixel Clock | 225 MHz |
| Compliance | HDCP 1.4 Compatible |
| Max. Resolution | Up to 1920 x 1200 |
| Max. Distance | Up to 5m |
| Control | |
| RS-232 | Connector: 1 x DB-9 Female (Black) Baud Rate and Protocol: Baud Rate: 19200, Data Bits: 8, Stop Bit: 1, Parity: No, Flow Control: No |
| IR | 1 x Mini Stereo Jack Female (Black) |
| Ethernet | 1 x RJ-45 Female (Black) |
| EDID Settings | EDID Mode: Default / Port 1/ Remix / Customized |
| Connectors | |
| Power | 1 x 3-Prong AC Socket |
| Power | |
| Maximum Input Power Rating | 100-240VAC; 50-60Hz; 1.0A |
| Power Consumption | AC110V:55.9W:262BTU/h AC220V:55W:258BTU/h Note: <ul style="list-style-type: none"> ● The measurement in Watts indicates the typical power consumption of the device with no external loading. ● The measurement in BTU/h indicates the power consumption of the device when it is fully loaded. |
| Environmental | |
| Operating Temperature | 0-50°C |
| Storage Temperature | -20 - 60°C |
| Humidity | 0 - 80% RH, Non-Condensing |
| Physical Properties | |

| | |
|------------------------|---|
| Housing | Metal |
| Weight | 4.25 kg (9.36 lb) |
| Dimensions (L x W x H) | 43.24 x 25.98 x 4.40 cm (17.02 x 10.23 x 1.73 in.) |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

Diagram



ATEN International Co., Ltd.

3F, No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767
 www.aten.com E-mail: marketing@aten.com



© Copyright 2015 ATEN® International Co., Ltd.
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.
 All rights reserved. All other trademarks are the property of their respective owners.